

Equipment Inventory - Solid Jacks-- Double Action

Item #	Capacity	Stroke	Area	Pressure	Height	O.D.	Rod Dia.	Oil Ca, cu/in	Weight, lbs
J5513D	55	13	11.04	9,091	19.85	5	2.65	143.5	90
J7524D	75	24	15.9	9,434	38	6.7 X6.7	2	118	200
J1006D	100	6	20.63	9,695	15.75	6.18	4	76	124
J1256D	125	6	23.76	10,395	13.38	7	4	82	125
J1506D	150	6	30.68	9,779	14.88	8.25	4.5	105.4	188
J15013D	150	13.13	30.68	9,779	21.38	8.25	4.5	209	259
J20013D	200	13	50.26	9,959	25.38	10	6.5	653.4	495
J2502D	250	2.25	47.17	9,779	8.94	9.5	5.88	60	167
J3556D	355	6	70.9	10,017	11.38	11.75	7.75	141.8	324
J40013D	400	13	95	8,421	26.28	12.63	7.25	770	625
J5006D	500	6.5	132.73	7,534	17.5	15.88	10	511	870
J5652D	565	2	113.1	9,991	14	15	9.75	168	670
J60012D	600	12	132.73	7,534	25.88	15.88	10	943	1200
J90012D	900	12	182.32	10,000	28	20	11.69	2,153	2,332